

SPECIFICATIONS

8'6"W x 24'L Transportable Comfort Station Wide Body Presidential Series

CHASSIS & FRAME:

Heavy duty 12" x 4" x 16 lb. structural steel main beams
2" x 2" x 16 ga. galvanized steel tubing floor joist 16" o.c.
Heavy duty extruded aluminum top rail
Two (2), axle with electric brakes and emergency breakaway kit
Four (4), tires with silver mod style wheels
One (1), 10,000 lb. tongue mounted frame jack
Four (4), 5,000 lb. leveling jacks, one at each corner of the trailer
2 5/16" ball hitch, bumper pull

EXTERIOR WALLS, ROOFING, & INSULATION:

2 x 4 wood wall studs installed 16" o.c.
2 x 6 wood roof rafters installed 16" o.c.
R-11 Batt insulation in walls, ceiling and floor
.040 aluminum extended siding with baked on white enamel finish, secured with stainless steel fasteners
.040 thick seamless aluminum roof fastened to the top rail with all fasteners penetrations located outside the unit to eliminate water leaks

INTERIOR WALLS, CEILING & FLOORING:

Simulated marble bonded to 3/8" plywood on all interior walls
Interior trimmed with stained wood base, chair rail and corner moldings
Seamless Fiberglass Reinforced Plastic bonded to 3/8" plywood on ceilings
3/4" marine grade tongue and groove plywood sub-floor
Vinyl floor finish, wood grain color

PLUMBING & INTERIOR FACILITIES:

Steel storage tank (sandblasted and painted with a cold tar epoxy) mounted under trailer with clean out and sight glass
A fresh water connection is included
A waste connection is included with 2" valve and cam lock fitting with cap
One (1), 6 gallon electric water heater

Men's Bathroom installation includes:

Fully enclosed stall with simulated marble walls, full length stained solid core wood door with polished brass handles, stained wood trim and shelf, indirect fluorescent lighting with stained wood valances, low consumption flushing toilets and polished brass paper holders
Wall hung porcelain urinal with polished chrome flush valves

Porcelain covered steel sink with lever handle faucets mounted in color
coordinated laminated countertop with locking oak vanity cabinets below
Large vanity mirror trimmed with stained wood
Roof vent with aerodynamic cover
Double glazed tinted sky light

Women's Bathroom installation includes:

Fully enclosed stalls with simulated marble walls, full length stained solid core
wood door with polished brass handles, stained wood trim and shelf,
indirect fluorescent lighting with stained wood valances, low consumption
flushing toilets and polished brass paper holders

Porcelain covered steel sink with lever handle faucets mounted in color
coordinated with cultured marble countertop (bone color) with locking oak
vanity cabinets below

Large vanity mirrors trimmed with stained wood
Roof vent with aerodynamic cover
Double glazed tinted sky light

ELECTRICAL:

Indirect fluorescent lighting with stained wood valances

Roof mounted A/C unit with 13,500 BTU cooling and 5,600 BTU heating ducted

Stereo system with AM/FM radio and CD player, includes 4 speakers
mounted in the ceiling, 2 in each restroom

Two (2), 20 amp NEMA 1 panel boxes, located in a separate lockable
compartment, 120V / 60 HZ / 1Ø

DOT approved running lights

Wall mounted exterior lights at Entry/Exit doors

DOORS & STEPS:

Heavy duty doors with an .080 thick extruded aluminum frame that sandwiches
galvanized steel inner cores, an aluminum exterior skin and a simulated marble
interior skin with continuous hinge, weathertite perimeter neoprene bulb seal, pull
handles, hydraulic closers and deadbolt locks

Exterior doors keyed alike

Aluminum drip rails installed over each exterior door

Two (2), sets of heavy duty fold-out telescopic wide steps, aluminum with steel
frame, extra large top step and fold out aluminum handrails with three point
support for strength

NOTE:

- 1. In a continuing effort to improve products, pricing and contents are subject to change without notice.**
- 2. Not included are soap dispensers, paper towel dispensers and trash receptacles.**
- 3. Engineered drawings and code compliance are not included in this quotation.**

